

Downlight 725.22 Flush mount WW General White

REF. 72522030-983



BASIC INFORMATION

DESCRIPTION

With optics for general photometric distribution and lighting LED efficient, sustainable, the downlight 725.22 Advance of the range Simon for indoor lighting, give your room a comfortable and uniform lighting. Its colour temperature of 3100 K for WW, creating environments warm and cosy in spaces and working areas such as offices, offices or reception areas, among its many possibilities. To sustainability that gives the LED technology and the control system of switching on ON-OFF, is coupled its performance of 2100 lm for WW, and total luminaire consumption of 24 W and compatibility with power supplies 100-240 Volts and 50-60 Hz for 30,000 hours of service life to 25 °C. With finishes in a stylish and white tones colour and designed for its installation, recessed, ensures integration with the space, providing a minimalist design with the highest lighting quality, functionality and innovation.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2100 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

2100 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

88 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.22

PRODUCT NET WEIGHT

1.22

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116708

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

250

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4375000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.22

PACKAGING NET WEIGHT

1.22

PACKAGING WEIGHT UNIT

KGM