

PD-8 PIR+LUX surface KNX black IP54

REF. 89212732-138



BASIC INFORMATION

DESCRIPTION

Presence and brightness surface PIR detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360°. The tangential detection range is 8 m and the radial detection range is 4.5 m.

The brightness regulation range is 2 - 800 lux. The configuration of the detector is performed through potentiometers and KNX.

It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 10 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. Black finish, protection rating IP 54 and dimensions: Ø 129 x 65 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342497

UNITARY PACKAGING GROSS WEIGHT

0.315

PACKAGING LENGTH

135

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.241

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1579500

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053342497

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.315

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

130

PACKAGING NET WEIGHT

0.241

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

90

PACKAGING WEIGHT UNIT

KGM