Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 6 FTP black Simon K45

REF. **KB96F/14**



BASIC INFORMATION

DESCRIPTION

With the elegance of avant-garde finishes in black, the plate of voice and data flat plate with dust cover with 1 element and 2 RJ45 category 6 FTP connectors,, in the collection Simon K45, it provides to their stay high speed data transmission, with a simple installation that facilitates cable management. With category 5e UTP and compatible with Keystone-type ports, the flat base plate Simon K45, maximize the functionalities of the product, at the same time that promotes the integration of the set in any type of space. Its installation, suitable for surface-mounted or recessed, is direct snap-fit without screws and, for an extra versatility, you can prepare in vertical enclosures thanks to 90 ° positioner (ref.K66) for an optimal orientation of the product. Manufactured in thermoplastic autoexinguible halogen-free, prevents the flame spread. Security, functionality and innovation in the Simon K45 range.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data flat plate with dust cover, RJ45 category 6 FTP connectors and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Supplied with voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

3891888

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.056

PRODUCT NET WEIGHT

0.056

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436047907

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

112

PACKAGING WIDTH

117

PACKAGING LENGTH

269

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3524976

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.56

PACKAGING NET WEIGHT

0.56

PACKAGING WEIGHT UNIT

KGM