Downlight 703.25 NW Wide Flood IP65 DALI White

REF. **70325330-484**



BASIC INFORMATION

APPLICATION

Hotel,Wet areas,Restaurants,Residential,Retail,Office,Healthcare,Education

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

CUT OFF
No

LUMENS/W
680 lm/7.5 W

IP RATING
IP65

DRIVER INCLUDED
Yes

OPTICS
Wide Flood

OPERATING TEMPERATURE RANGE (ºC)
15 - 35 ºC

L70 (ºC)
30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER SUPPLY (V~)
100/240 V~

LIGHT BEAM APERTURE ANGLE (°)
40º

POWER (W)
7.5 W

COLOR TEMPERATURE (K)
4000 K

COLOR TYPE
NW

SERVICE LIFE
30.000 h

CONTROL
DALI

LIGHTING EFFICIENCY (LM/W)
91 lm/W

CRI
80

LUMENS (LM)
680 lm

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053285312

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.401

PRODUCT NET WEIGHT
0.28

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053285312

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.401

PACKAGING NET WEIGHT
0.28

PACKAGING WEIGHT UNIT
KGM