


Linear luminaire 5550 BT Mesh 42W 3000K 5-wire with detector 24GHz 8m HF+LUX IP44

REF. 89353620-423



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector, 5-wire and Bluetooth connectivity. Power is 31.0 W, luminous flux is 5768 lm and colour temperature is 3000 K. Maximum installation height is 4 m, surface-mounted.

Detection range is 8 m and detection angle is 360°.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The luminaire is configured via a Bluetooth app. Luminaires can be interconnected via Bluetooth mesh.

Supply voltage is 220 - 240 VAC. Operating temperature: -20 - 40 °C.

Protection rating IP 44 and IK 07, dimensions: 1500 x 164 x 75 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP44

CONTROL

BT

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053465851

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053465851

PACKAGING VOLUME

20071800

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

90

PACKAGING GROSS WEIGHT

2.95

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

177

PACKAGING NET WEIGHT

2.45

UNITARY PACKAGING GROSS WEIGHT

2.7

PACKAGING LENGTH

1260

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.45