Projector 889 100W 4000K

REF. **88933038-884**



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for illuminating shop windows and facades, robust, adjustable, and designed for high performance in commercial applications. Available in different wattages, the outdoor projector 889 allows for the selection of the appropriate model based on mounting height, surface to be illuminated, and desired impact level. Installation type: Surface. Optics: 110. Color temperature: 4000K. Power: 100W. Lumens: 9000lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 256 mm x 229 mm x 42 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
90 lm/W

LUMENS (LM)
9000 lm

OPTICS
Symmetric

POWER (W)
100 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440360

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.024

PRODUCT NET WEIGHT
0.97

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440360

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
255

PACKAGING WIDTH
210

PACKAGING LENGTH
280

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
14994000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
4.096

PACKAGING NET WEIGHT
0.97

PACKAGING WEIGHT UNIT
KGM