IP66 Mechanism holder and security frame for K45 mechanism and RJ45 Keystone lodge

REF. **KFH101SEC/74**



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of waterproof floor boxes for indoor and outdoor environments. This is a mechanism frame with a security lock for environments that require restricted access, with capacity for 1 K45 function of 45x45mm and RJ45 Keystone connector. In combination with its housing, it will allow installation in raised floors or pavement. The product design, coupled with its manufacture from stainless steel, ensures a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm^2 from any direction, achieving an IP66 protection rating when the cover is closed. It also supports a maximum load of 1500 kg and resistance IK08 to impact. It maintains an optimal cable bend radius in high-category voice and data connections. Our accessory for plug connection with closed cover is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the possibility of leveling our box in case of having an uneven floor (see reference KFA1003), or the capability to link more than one box (see reference KFA1002).

FINISH

Black

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

RJ45

KIT AVAILABILITY

Yes

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

IK CLASSIFICATION

08

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IP RATING

IP66

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE FRAME

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60670-23:2008|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053332696

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.14

PRODUCT NET WEIGHT
0.113

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053332696

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
114

PACKAGING WIDTH
124

PACKAGING LENGTH
130

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1837680

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.14

PACKAGING NET WEIGHT
0.113

PACKAGING WEIGHT UNIT
KGM