Complete in-desk kit with double-opening lid with metal flap, 6 Schuko sockets and plate for 4 RJ45 connectors, black, Simon 400 Indesk Duo

REF. **47403020-138**



BASIC INFORMATION

DESCRIPTION

Thanks to this complete kit integrated into the table with a double opening cover, fins, and 6 schuko socket bases and plates for 4 RJ45 in black from the Simon 400 Indesk Duo series, we can have all the necessary connections without the need for long cables on the floor. A piece of cutting-edge design and high-quality materials such as painted steel for the casing or anodized aluminum for the profile, these materials provide the necessary durability to last many years like the first day. Manufactured for 250 volts and a current intensity of 16 amps, it features a Wieland® gst18i 3-pole male aerial connector with a 22 cm patch cord. It has a manual lifting system for easy access to its 6 bases for standard current circuit. Simon is characterized by its safety, an example of which are the covers and fastenings made of halogen-free self-extinguishing thermoplastic, which guarantee the non-propagation of flames and prevent the creation of toxic fumes.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

RECESS DIMENSION (MM)
228 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS
4

SNAP-FIT RJ45 PLATES
Keystone I, II and Systimax

SNAP-FIT TYPE
Keystone I, II and Systimax

NUMBER OF SOCKETS
6 sockets for standard current circuit

VERSION
8 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With metal fin

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45º and 135º

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053208625

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.45

PRODUCT NET WEIGHT
2.45

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053208625

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
370

PACKAGING WIDTH
135

PACKAGING LENGTH
200

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
9990000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.45

PACKAGING WEIGHT UNIT
KGM