

Kit Flash 90 consisting of schuko modular power socket, USB charger Type C 100W (distributed in 65+30W if connected at the same time) and grommet (cable outlet) white Simon K45

REF. KR3510001/9



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular schuko power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and conceal the connections when not in use. Includes a 100W USB Type-C charger (distributed to 65+30W if connected simultaneously) and a cable outlet in white finish. Supplied with a 20cm long cable tie terminated with a 3-pole Wieland® Gst18i male quick-connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. All that is required is to cut the hole in the furniture where the product will be mounted. Once this is done, connect it to the mains power supply for operation.

FINISH

White

MATERIAL

Plastic

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

SNAP-FIT RJ45 PLATES

No

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

IP RATING

IP20

SNAP-FIT TYPE

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CHARACTERISTICS

Charging

RJ45 CONNECTORS

No

NOMINAL VOLTAGE (V~)

250 V~

USB CURRENT (A)

20 A

CONNECTOR TYPE

Schuko

RAL

9003

POWER DELIVERY USB

Yes

NUMBER OF CONTACTS

3

RECESS DIMENSION (MM)

ø80 mm

QUICK CHARGE USB

Yes

FORMAT

Schuko

RJ45 ADAPTOR MODULE

No

USB VOLTAGE (V~)

5 V~

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

No tools needed

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

REMOVAL OF COVER

Only with tool

Quick connector

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 | Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053398500

UNITARY PACKAGING GROSS WEIGHT

0.211

PACKAGING LENGTH

252

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.192

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3931200

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053398500

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.753

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

120

PACKAGING NET WEIGHT

0.192

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM