

## Adjustable floor box kit raised floor 6 elements with double socket, dual UPS, 2 plates 1 RJ45 3M® grey Simon 500 Cima

REF. 52006309-030



## BASIC INFORMATION

### DESCRIPTION

Kit for adjustable floor box and for six elements: Double socket, double UPS and 2 RJ45. With grey finish, the article measures 226 x 187 x 92 mm and consists of metal components with halogen-free thermoplastic insulation, this material is self-extinguishing, which means that, in the event of a fire notional, prevent the flames from spreading. The kit is specially designed to be installed in raised floor. If you wish, you can be combined with the flush-mount trim cover if not installing the same floor lining. The kit corresponds to the Simon 500 Cima series and offers a click terminal connection. Therefore, simply insert, tighten and ready, and does not need to strip cables. All the kits in this collection are delivered is properly assembled and wired. For cleaning, use a soft, dry cloth.

### FINISH

Grey

### COMPATIBILITY

Simon 500 CIMA mechanisms

### ETIM CLASS

EC000024

### MATERIAL

Plastic

### PACKAGING CONTENTS

Kit, metal partition wall, ground connection cable, screws and installation manual

### REMARKS

To complete the installation of the product, as an option, it may be combined with flush-mount trim cover (ref.52053103-035) in cases where the same floor lining is not installed.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

### NUMBER OF CLAMP-HOLDER HOLES

8

### NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for the fast terminal connection system

### COMPATIBLE WITH CONNECTORS

3M® Volition OCK, RJ25, K5e and K6

### NUMBER OF CONNECTORS

2

### RJ45 CONNECTORS

Not included

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

### DUST SHUTTER

No

### ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

### IK CLASSIFICATION

08

### INDICATOR FUNCTION

Yes

### INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

### CURRENT (A)

16 A

### IP RATING

IP4X

### LED CONSUMPTION INDICATOR (mA)

0.55

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### MAXIMUM LOAD (KG)

1700kg

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### TYPE OF MECHANISM

Insertion

### NUMBER OF MODULES

6 modules

### NUMBER OF PLATES

2 voice and data plates

### PLATE TYPE

Flat

### RAL

7011

### RECESS DIMENSION (MM)

170 x 210 mm

### RJ45 ADAPTOR MODULE

Included in voice and data plates

### NUMBER OF SIDE ENTRANCES

12

### SNAP-FIT RJ45 PLATES

3M

### SNAP-FIT TYPE

3M

### NUMBER OF SOCKETS

2 double sockets: 1 double socket for standard current circuit and 1 double socket for stable current circuit

### VERSION

6 elements

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

0

### CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

### REMOVAL OF CONNECTOR

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

### TYPE OF FASTENING

Using fastening claws on the raised floor tile (supplied with the floor box)

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Specially designed to be installed in raised floors

### REMOVAL OF THE PLATE

Only with tool

### REMOVAL OF THE SOCKET

Only with tool

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

### NUMBER OF TERMINALS

3 inputs and 3 outputs

## REGULATIONS

### REGULATIONS

UNE-EN 60.670-23

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053112625

### PRODUCT NET WEIGHT

1.56

### PACKAGING LENGTH

0

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

0

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8421053112625

### PACKAGING GROSS WEIGHT

0

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING NET WEIGHT

1.56

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

0

### PACKAGING WEIGHT UNIT

KGM

### UNITARY PACKAGING GROSS WEIGHT

1.56

### PACKAGING WIDTH

0