

2-way switch for card with 1 micro switch and light indicator 250V~ graphite Simon 75

REF. 75526-38



BASIC INFORMATION

DESCRIPTION

The 2-way switch for card switch with a microswitch part of the collection of mechanisms of the Simon 75 series, with its finished in graphite, it incorporates an indicator light. Composed by an element in its individual version adapts to its function perfectly. With reference 75526-38. With an intensity of 6 A and a voltage of 250V~ The installation can be perform either in surface-mounted and in any universal recessed box. Its operation is per card and the rocker operation is fast operation. The cross-cable section is 0.5mm. It is made by several metal components with a halogen-free insulation. It incorporates a trim made of thermoplastic.

FINISH

Graphite

PACKAGING CONTENTS

Mechanism and cover

COMPATIBILITY

Simon 75 frames

ETIM CLASS

EC001590

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connection with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

POWER SUPPLY (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.08

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3017190

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053044285

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.4

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.4

UNITARY PACKAGING GROSS
WEIGHT

0.08

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223