

Monoblock floor trunking 2.75m and 130x18mm with 3 compartments

REF. TF21183/8



BASIC INFORMATION

DESCRIPTION

The monoblock DCS TF21183/8 floor trunking is a robust and secure option for cable distribution indoors, especially in commercial and industrial environments. Made of aluminum with an anodized finish, it has a 130x18 mm profile and offers a high IK08 impact protection rating. Its maximum load capacity is 75 kg/cm², making it suitable for areas with constant traffic. The installation system ensures solid fixing on non-combustible floors, and the monoblock design provides greater security by keeping the trunking completely closed and inaccessible once installed, complying with UNE-EN 50085-1 standards.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION

08

KIT AVAILABILITY

No

RAL

7035

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436035621

PACKAGING VOLUME

50160000

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

11

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

150

PACKAGING GROSS WEIGHT

1.35

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

110

PACKAGING NET WEIGHT

14.795

PRODUCT NET WEIGHT

1.345

PACKAGING LENGTH

3040

PACKAGING WEIGHT UNIT

KGM