

## Spotlight 880.32 industrial 3000 K SYM

REF. 88032038-173



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### PACKAGING CONTENTS

1 unit

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

70

### LIGHTING EFFICIENCY (LM/W)

121 lm/W

### IK CLASSIFICATION

08

### DIRECTIONAL

Yes

### LUMENS (LM)

12100 lm

### IP RATING

IP65

### DRIVER INCLUDED

Yes

### LUMENS/W

12100lm/ 100W

### OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

### L70 (°C)

100,000 h at 25 °C

### OPTICS

Symmetric

### POWER SUPPLY (V~)

100/240 V~

### L90 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3000 K

### LIGHT BEAM APERTURE ANGLE (°)

90°

### POWER (W)

100 W

### CONTROL

On/Off

### COLOR TYPE

WW

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Surface (with bracket)

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053205464

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

5.688

### PRODUCT NET WEIGHT

4.14

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053205464

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

135

### PACKAGING WIDTH

485

### PACKAGING LENGTH

395

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

25862625

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

5.688

### PACKAGING NET WEIGHT

4.14

### PACKAGING WEIGHT UNIT

KGM