

Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP white Simon 500 Cima

REF. 50003085-030



BASIC INFORMATION

DESCRIPTION

Model of voice and data plate Number of the range 50003085-030 professional components and elements Simon 500 Cima, Designed to meet the needs and installation of different systems, compatible With other components and elements of the same Simon 500 Cima series. Type of flat base plate of voice and data with dust cover for 1 item For an RJ45 connector category 6 FTP format snap-fit Keystone I, II, ATT ® / Avaya ®. Integrated in its composition elements to minimize the risk of Situations of the flame and smoke contaminants. Compatibility for fastening In vertical and horizontal enclosures without the need of presents adaptor. Dimensions of 50 x 50 x 45,4 mm and a depth Of 45,4mm, element versatile for all types of connectors And voice and data connections.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 FTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098011

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.036

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.72

PRODUCT NET WEIGHT

0.036

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

