

PD-6x6 Micro PIR+LUX recessed DALI-2 Input white IP65

REF. 89219311-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted presence and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 6 x 6 m and the radial detection range is 4 x 4 m. The brightness regulation range is 2 - 1000 lux. The configuration of the detector is done via DALI. It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 4 mA. The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -25 - 55 °C. White finish, IP 65 protection rating, and dimensions: Ø 43 x 75 mm. 5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP65

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343142

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.154

PRODUCT NET WEIGHT

0.132

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343142

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

90

PACKAGING LENGTH

120

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

810000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.154

PACKAGING NET WEIGHT

0.132

PACKAGING WEIGHT UNIT

KGM