

USB charger (4.2 A) of 1 element K45 type "A+C" in aluminum Simon K45

REF. K126G/8



BASIC INFORMATION

FINISH

Aluminium

MATERIAL

Thermoplastic

COMPATIBILITY

Can only be used with function structures from the K45 family, except in IP66 watertight floor boxes. The Simon 500 Cima to Simon K45 adapter is not compatible with this reference.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

RECESS DIMENSION (MM)

40

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CHARACTERISTICS

21W

CONNECTOR TYPE

USB A + USB C

USB CURRENT (A)

4,2 A

NUMBER OF CONTACTS

2

NOMINAL VOLTAGE (V~)

230 V~

USB VOLTAGE (V~)

5 Vdc

FORMAT

USB A + USB C

POWER SUPPLY (V~)

230 V~

NUMBER OF WIRES

2

INDICATOR FUNCTION

Yes

RAL

9006

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

REMOVAL OF CONNECTOR

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 2

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053288429

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053288429

PACKAGING VOLUME

68138

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

56

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

15.5

PACKAGING NET WEIGHT

0.082

UNITARY PACKAGING GROSS
WEIGHT

0.082

PACKAGING LENGTH

78.5

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.082