

Modular luminaire 720 Advance M4 120x30 NW CLC

REF. 72061440-684



BASIC INFORMATION

DESCRIPTION

With the luminaire 720 modular Advance M4 of the range of indoor lighting of Simon, you will get the perfect balance between functionality, innovation and energy savings. With constant light control (CLC) and optics micro prismatic anti-deslumbramientos, dim the natural light armonizándola with its light artificial. With a luminous light flux 3400 lumens for NW, has a consumption of luminaire 28 W, and thanks to its multiple LEDs, with a service life of 100,000 hours for the L70 at 25 ° C and L90 40.000 for. This luminaire is compatible with power Volt voltage 100-240 and frequency of 50-60 Hertz rate. With a compact dimension of 120 x 30 mm and finishes in white, its installation is suitable for both flush mounted and surface-mounted in false ceiling and hardware, guaranteeing the integration of the set in all types of spaces, adapting to the specific needs technical and aesthetics.

DIFFUSER MATERIAL

PMMA

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

CLC

LIGHT BEAM APERTURE ANGLE (°)

124°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.45

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8436547069941

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

0

PACKAGING WIDTH

0

PACKAGING LENGTH

0

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

5