

Simon SM34 Wall Charging Point with 5m Cable T2 Three-Phase 22 kW + Bluetooth + Automatic and Differential

REF. 0651022-200



BASIC INFORMATION

FINISH

Graphite

APPLICATION

Residential

ETIM CLASS

EC002883

MATERIAL

ABS Plastic

OPERATING ENVIRONMENT

Residential

TECHNICAL INFORMATION

CONNECTOR TYPE

Type 2 Straight cable

CURRENT (A)

32 A

MODE 3 STATUS INDICATOR

Yes

FREQUENCY

50 Hz

IP RATING

IP54

NUMBER OF OUTLETS

1

IK CLASSIFICATION

10

TYPE OF LINE

Three-phase

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/53/UE RED*1 | EN IEC 61851-1:2019 | EN IEC 61851-21-2:2021 | EN 62196-2:2017 | EN 62311:2008 | EN IEC 63000:2018 | ETSI EN 300 328 v2.2.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053301289

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

6.3

PRODUCT NET WEIGHT

6.3

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053301289

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

149

PACKAGING WIDTH

408

PACKAGING LENGTH

580

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

35259360

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

6.3

PACKAGING NET WEIGHT

6.3

PACKAGING WEIGHT UNIT

KGM