

Spotlight 640.10, Flush mount Amber Spot Black

REF. 64010038-282



BASIC INFORMATION

DESCRIPTION

Simon continuously at the level of technological and done extensive studies through its test laboratories to obtain results of maximum quality in with the most rigorous. In addition, its R +D + i laboratory creates new product lines the meet the demands of the market. Thus they created the range of 640 spotlights. With different colour ranges, and different optics to solve all areas of lighting, both of general and directed. Its minimalist design offers a varied and its high versatility give you the option of solve all kinds of professional lighting in different environments. Excellent in retail, exhibition halls zones, shopping areas with specific products, museums, etc. This is of a spotlight for indoor lighting. Spotlight 640 Rail Amber SPOT Black category B. Colour. 640 spotlights. Colour temperature Amber 2500 K SPOT Optics, which directs the light beam to 15 °, allowing light to be focused on specific places or products. Light intensity 2100 lm / 23 W. Durability 30,000 h at 25 ° C. 120-240 V 50 / 60 Hz. ON-OFF switch system . Without flashes, lighting 100% instant, which prevents the visual fatigue. Temperature that allows 35 ° C maximum. Weight 1.4 kg. For placing in 3-phase rail, provided separately. Dimensions 100x102 mm

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

2600 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2600 lm/30W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

ELECTRICAL CLASS

Type 1

OPTICS

Spot

POWER SUPPLY (V~)

120/240 V~

L70 (°C)

100,000 h at 25° C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

2500 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

30 W

CONTROL

On/Off

COLOR TYPE

Amber

SERVICE LIFE

50.000 h

LIGHTING EFFICIENCY (LM/W)

87 lm/W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.4

PRODUCT NET WEIGHT

1.184

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053138038

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

200

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

8000000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.4

PACKAGING NET WEIGHT

1.184

PACKAGING WEIGHT UNIT

KGM