Extension 0.5 metres for aluminium column with 2 sides oval Simon K45

REF. **ALK72P05/8**



BASIC INFORMATION

DESCRIPTION

Model of element for Pole for fastening to the floor reference ALK72P05 / 8, It is part of the range of products and components of the series Simon professional 500 Cima, suitable for different environments and installations work Professionals and domesticas. It is an extension, 0.5 Meters for pole for fastening to the floor of 2 sides oval Simon K45, with the maximum Guarantees of solidity and versatile for different systems for fastening. Manufactured in aluminium material, Available finishes in colour and tone metal. Measures 500 x 80 x 110 mm, suitable For elements of different kinds of surfaces and environments. Work professionals.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+120º C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (ºC)
+650ºC (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-25 a 120º C

VERSION
2-sided (Oval)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical

REGULATIONS

REGULATIONS
UNE-EN 50.085-2-4-:2006

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050549

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
1.5

PRODUCT NET WEIGHT
1.5

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436050549

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
90

PACKAGING WIDTH
120

PACKAGING LENGTH
540

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5832000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.5

PACKAGING NET WEIGHT
1.5

PACKAGING WEIGHT UNIT
KGM