

PD-10 PIR+US recessed KNX white IP20

REF. 89252713-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush-mounted PIR + US. The recommended installation height is 2.8 m, with a maximum height of 3.5 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 10 m and the radial detection range is 10 m. The brightness regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The configuration of the detector is done through potentiometers and KNX. It features a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 17.5 mA. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -25 - 55 °C. White finish, protection rating IP 20 and dimensions: 120 x 120 x 103 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053381571

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.335

PRODUCT NET WEIGHT

0.19

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053381571

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

140

PACKAGING WIDTH

140

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.335

PACKAGING NET WEIGHT

0.19

PACKAGING WEIGHT UNIT

KGM