

## Downlight 725.23 Flush mount NW General IP44 White

REF. 72523930-984



### BASIC INFORMATION

#### DESCRIPTION

This product is part of the downlights of the range 725 Category A of the brand Simon, characterized by its high lighting capacities and high quality of materials. The Downlight 725.23 Advance provides a neutral light (NW) thanks to its optics GENERAL- IP44. Its dimensions of 165 x 51 millimetres and its traditional white colour make it capable of adapting to any room and place that you want to be lit. In addition, its size and easy installation by means of recessed in the wall or ceiling, makes it possible to combine with other products of lighting in the same features, according to the needs of the space where it is placed. It has a colour temperature of 3,900 K and, at 1300 lumens and 14 Watts, and its control is performed by the classic and effective system ON / OFF requires a power supply of 100-240 volts and 50 / 60 Hertz rate of frequency for proper operation. This downlight stands out for its high quality materials, which means that it can operate and light rooms, without losing efficiency, low temperatures very low and high, ranging from - 15 to 40 degrees centigrade.

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

1300 lm

### IP RATING

IP44

### ELECTRICAL CLASS

Type 1

### LUMENS/W

1300 lm/14W

### OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

### INTEGRATED POWER SUPPLY

Yes

### OPTICS

General

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3900 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

14 W

### CONTROL

On/Off

### COLOR TYPE

NW

### SERVICE LIFE

30.000 h


### CRI

80

### LIGHTING EFFICIENCY (LM/W)

93 lm/W

### CHROMATICS CRI ICONS



## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface

### INSTALLATION TYPE

Flush mount

### MINIMUM INSTALLATION HEIGHT

101

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053116890

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.616

### PRODUCT NET WEIGHT

0.616

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053116890

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

80

### PACKAGING WIDTH

195

### PACKAGING LENGTH

195

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3.042

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.616

### PACKAGING WEIGHT UNIT

KGM