

## 2-way switch for card with 1 micro switch and light indicator 250V~ aluminium Simon 75

REF. 75526-33



## BASIC INFORMATION

### DESCRIPTION

This Simon 75 series includes multiple options of design, thanks to all the combinations of colours (different finishes for rockers, parts pieces and frames) and also of shapes, as it has a rectangular design that adapts to two different shapes. A 2-way switch is a switch that the 2-way switch, each time a detached circuit, connected to another. That 's why for Simon are all important. This 2-way switch for card with 1 microswitch and indicator light (its code is the 75526-33) resists elements up to 6 Amps and 250 Volt. Its finish is in aluminium. As far as its installation is concerned, we recommend that you do in combination with a contactor / relay. If not makes this way, remember that the maximum current of the 2-way switch is 6 Amps (2nd inductive). In terms of the installation of the frame, remember to break the flanges.

### FINISH

Aluminium

### PACKAGING CONTENTS

Mechanism and cover

### COMPATIBILITY

Simon 75 frames

### ETIM CLASS

EC001590

### REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INDICATOR FUNCTION

Yes

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### CABLE SECTION ADMITTED (MM)

0,5 mm

### CURRENT (A)

10 (1,5 ind.) A

### POWER SUPPLY (V~)

250 V~

### CONSUMPTION INDICATOR (mA)

1 mA

### IP RATING

IP20

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### VERSION

Single

### FREQUENCY

50 Hz

### TYPE OF MECHANISM

Card

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW

Simon 27

### INSTALLATION DIRECTION

Horizontal, Vertical

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### INSTALLATION TYPE

Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

PRODUCT NET WEIGHT  
0.075

PACKAGING MEASUREMENT  
UNIT  
MMT

UNITARY PACKAGING WIDTH  
0

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING VOLUME  
3017190

UNITARY PACKAGING LENGTH  
0

PACKAGING EAN  
8421053017951

PACKAGING VOLUME UNIT  
MMQ

UNITARY PACKAGING VOLUME  
1517738

UNITS CONTAINED PACKAGING  
5

PACKAGING GROSS WEIGHT  
0.375

UNITARY PACKAGING VOLUME  
UNIT  
MMQ

PACKAGING HEIGHT  
82

PACKAGING NET WEIGHT  
0.375

UNITARY PACKAGING GROSS  
WEIGHT  
0.075

PACKAGING WIDTH  
83

PACKAGING WEIGHT UNIT  
KGM

PACKAGING LENGTH  
223