

Front trim cover 3 metres for columns aluminium Simon K45

REF. RALK013/8



BASIC INFORMATION

DESCRIPTION

The trim front cover of the Simon K45 range is ideal for columns of three metres of the same range in aluminium finish. This is the perfect to integrate a column of these features in the ambience of the room or department where it is installed, making the most of the element in a place without break with the decorative line. This front cover is easy to install and maintenance, and also has multiple possibilities since it is compatible with several products: Columns of one side of the two sides, square, columns and columns of four faces. Its manufacturing with anodised steel makes it highly resistant to possible knocks and scratches. To do this, the usual steel we electrochemical to a process which results in this material of great durability, which duplicates the hardness and robustness of stainless steel and that extends considerably the service life of the product.

FINISH

Metal

PACKAGING CONTENTS

Front trim cover

MATERIAL

Aluminium

ETIM CLASS

EC000461

REMARKS

Product envisaged as a replacement part, in the event of loss or substitution. It is compatible with the 1-sided, 2-sided square and 4-sided columns. Supplied extruded in anodised aluminium.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

EARTHING RESISTANCE

< 0.05 ?

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

AVAILABLE IN

1-sided, 2-sided (square and oval) and 4-sided

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

VERSION

1-sided, 2-sided (Square) and 4-sided

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

IP RATING

IP4X

KIT AVAILABILITY

No

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Through direct snap-fit on the column (does not require the use of tools for fastening)

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056442

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436056442

PACKAGING VOLUME

10.872

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

60

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

60

PACKAGING NET WEIGHT

1.225

UNITARY PACKAGING GROSS WEIGHT

1.225

PACKAGING LENGTH

3020

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.225