

ARCH Downlight X-Less Accessory Square 1-10 V

REF. 91591119-999



BASIC INFORMATION

APPLICATION

Domestic, Office, Retail, Hotel, Contract Unit

PACKAGING CONTENTS

1 Unit

PACKAGING DIMENSIONS (MM)

90x115x169 mm

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CONTROL

1-10 V, Push Dim

ENERGY EFFICIENCY

A+

IP RATING

IP20 / IP43

COS Φ

0.94

LIGHTING EFFICIENCY (LM/W)

111 lm/W

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DIRECTIONAL

No

PHOTOBIOLOGICAL CLASSIFICATION

Class II

POWER SUPPLY (V~)

110/240 V~

DRIVER INCLUDED

No

POWER FACTOR (Φ)

> 0,9

ELECTRICAL CLASS

II

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted, Surface-mounted

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547036752

PRODUCT NET WEIGHT

2

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.028

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547036752

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.326

UNITARY PACKAGING VOLUME

2.475

PACKAGING HEIGHT

100

PACKAGING NET WEIGHT

2

UNITARY PACKAGING VOLUME UNIT

DMQ

PACKAGING WIDTH

160

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2

PACKAGING LENGTH

175