

Voice and data flat plate with dust cover for 1 element for 1 Nexans® RJ45 connector black Simon K45

REF. K85/14



BASIC INFORMATION

DESCRIPTION

The sound is a very important element to create the ambience more suitable for each situation. For the protection of these systems, we have the best ally in the flat plate for voice and data with dust cover for an element for an RJ45 connector Nexans in black colour of the series Simon K45. This accessory dimensions 45 x 45 x 8 ' 5 mm, being suitable for surface-mounted and recess. When combining the voice and data plate in vertical enclosures (mini-columns, columns, Teleblock, channels, mechanism holders) you must use the 90° positioner (reference K66) to guide the plate into a vertical position. The structure keeps its qualities as the first day thanks to the halogen-free thermoplastic, a component that guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

Half

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

IP RATING

IP20

RAL

7021

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Nexans® RJ45 connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

SNAP-FIT TYPE

Nexans® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.011

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032446

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

45570

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.22

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.22

UNITARY PACKAGING GROSS WEIGHT

0.011

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140