

Standard button box 6 functions with KNX coupling unit and slide control regulator graphite Simon 82 Sense

REF. 8400671-038



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Thermoplastic

ETIM CLASS

EC000672

SYMBOL

Dot

PACKAGING CONTENTS

Coupling unit, keypad, Slide Control, RJ12 cable and instructions

REMARKS

Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TYPE OF MECHANISM

Touch

NUMBER OF POSSIBLE ELEMENTS

2 elements

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

INDICATOR FUNCTION

Yes

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

INSTALLATION AND MAINTENANCE

BUS CABLE SECTION ADMITTED (MM)

From 0.5 to 0.8 mm

CABLE STRIPPING NECESSARY (MM)

8

INSTALLATION TYPE

Suitable for surface and flush mounting

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CLAW

Optional

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016 + + + + + +

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053129432

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.17

PRODUCT NET WEIGHT

0.17

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053129432

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

82

PACKAGING WIDTH

82

PACKAGING LENGTH

120

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

806880

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.17

PACKAGING NET WEIGHT

0.17

PACKAGING WEIGHT UNIT

KGM