

2-way switch 16AX 250V~ for half element with fast terminal connection system ivory Simon 27 Play

REF. 27211-61



BASIC INFORMATION

DESCRIPTION

Provide maximum functionality and innovation with the 2-way switch half element of the Simon 27 Play collection, with finishes in ivory, this 2-way switch of quick terminal connection, it adapts to any type of spaces thanks to its size 22.5 x 45 mm and its installation is suitable for recessed or surface-mounted. With 1 module for half an element, it is composed of metal materials with thermoplastic isolated, halogen free and thermo-stable trim for a longer and more efficient protection of the room in case of fire. This 2-way switch with rocker function, it is compatible with a voltage of power of 250 Volt and a current of 16 AX and supports a wire cross-section of 1.5 to 2, 5 mm and stripping of 11 mm Compatible with the most common frames and mechanisms of the range Simon 27, allows you to replace the finish of rocker included for any other of 5 within the collection.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 5 additional finishes available.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP21

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053251850

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

365040

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.028

PRODUCT NET WEIGHT

0.028

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053075586

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

54

PACKAGING WIDTH

52

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.012

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

0.14

PACKAGING NET WEIGHT

0.14

PACKAGING WEIGHT UNIT

KGM