

Downlight 703.24 Square Orientable NW Wide Flood DALI White

REF. 70324330-484



BASIC INFORMATION

APPLICATION

Hotel, Restaurants, Residential, Retail, Office, Healthcare, Education

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CUT OFF

Yes

LUMENS/W

700 lm/7.5 W

IP RATING

IP20

DRIVER INCLUDED

Yes

OPTICS

Wide Flood

OPERATING TEMPERATURE RANGE (°C)

15 - 35 °C

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

LIGHT BEAM APERTURE ANGLE (°)

40°

POWER (W)

7.5 W

COLOR TEMPERATURE (K)

4000 K

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CONTROL

DALI

LIGHTING EFFICIENCY (LM/W)

94 lm/W

CRI

80

LUMENS (LM)

700 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush-mount

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053089200

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.401

PRODUCT NET WEIGHT

0.28

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053089200

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

110

PACKAGING WIDTH

135

PACKAGING LENGTH

170

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2524500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.401

PACKAGING NET WEIGHT

0.28

PACKAGING WEIGHT UNIT

KGM