


Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6A FTP aluminium Simon 500 Cima

REF. 50001089-033



BASIC INFORMATION

DESCRIPTION

The Simon 500 Cima range is a leader in the development of plates for voice and data connections. All the accessories of this series stand out for their security, design and functionality, such as the flat plate for voice and data with dust cover for an element category 6A FTP in aluminium finish, a piece that has two connectors RJ45 with snap-fit basic Keystone I, II, ATT / Avaya. This accessory in individual version has dimensions of 50 x 50 x 44 mm, a cabling 22-24 AWG and RJ45 adaptor module included in the plate of voice and data. Metallic components with halogen-free. Its structure has been made with self-extinguishing thermoplastic and halogen-free, very safe and resistant material that guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6A FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097847

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.106

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

2.12

PRODUCT NET WEIGHT

0.106

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

