

Extension 1.5 metres for aluminium column with 1 side white Simon 500 Cima

REF. 53555103-030



BASIC INFORMATION

DESCRIPTION

In the fixed to ceiling category we find this extension of painted aluminium 1 side designed for a column and with white finish, the article has dimensions of 1500 x 110 x 72 mm and it corresponds to the Simon 500 Cima series, a collection that focuses on connectivity and ensure high speed data transmission. This extension has been manufactured in compliance with current regulations and is suitable for installation in any type of floor, regardless of whether it is raised or concrete flooring. The column can be fastened using a telescopic guide attached to the ceiling slab. To ensure the robustness of the total structure, it is only possible to combine one extension per column. To maintain the piece, it is advisable to use a soft and dry cloth, avoiding abrasive cleaners containing chlorine.

FINISH

White

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

RAL

9003

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using connecting pins

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for installing in any floor type, raised or concrete. Column secured by applying pressure to the ceiling slab using a telescopic guide.

REMOVAL OF TRIM FRAMES

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101865

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3.4

PRODUCT NET WEIGHT

3.4

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053101865

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

88

PACKAGING WIDTH

119

PACKAGING LENGTH

3040

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

31.835

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

3.4

PACKAGING WEIGHT UNIT

KGM