

Sound centre with 2 trunkings

REF. 05041-39



BASIC INFORMATION

COMPATIBILITY

Simon 75 mechanisms

PACKAGING CONTENTS

Sound centre, flush-mount box, RCA cable, 2 RCA adaptors and instruction sheet

REMARKS

The article includes flush-mount box.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

POWER SUPPLY (V~)

230 V~

CABLE SECTION ADMITTED (MM)

From 0,25 to 1,5 mm

TYPE OF MECHANISM

Push

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

FREQUENCY

50 - 60 Hz

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

NUMBER OF WIRES

11

INDICATOR FUNCTION

Yes

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

6

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Own

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

UNE-EN 60065:2003 + UNE-EN 55013:2002 + A1:2004 + UNE-EN 61000-3-2:2006 + UNE-EN 55022:2000 + UNE-EN 61000-4-3:2003 + A1:2004 + UNE-EN 61000-4-4:2005 + UNE-EN 61000-4-11:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

PRODUCT NET WEIGHT
1.335

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING VOLUME
2868750

UNITARY PACKAGING LENGTH
0

PACKAGING EAN
8421053059074

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

UNITS CONTAINED PACKAGING
1

PACKAGING GROSS WEIGHT
1.335

UNITARY PACKAGING VOLUME
UNIT
MMQ

PACKAGING HEIGHT
85

PACKAGING NET WEIGHT
1.335

UNITARY PACKAGING GROSS
WEIGHT
1.335

PACKAGING WIDTH
125

PACKAGING WEIGHT UNIT
KGM

PACKAGING LENGTH
270