Extension 1.5 metres for aluminium column with 2 sides Simon 500 Cima

REF. **53555203-033**



BASIC INFORMATION

DESCRIPTION

What you are looking for fixed to ceiling with the highest quality at the best price? Then is in the appropriate site. Complying both features, the extension of 1.5 metres for pole aluminium of two sides of the Simon 500 Cima series is one of the most demanded products in this range to include in projects masonry new and refurbishment projects in private homes, commercial premises or the headquarters of companies. Suitable for installing on any floor type, whether raised or concrete flooring, the fastening of the pole is performed using a telescopic guide attached to the ceiling slab. We are looking at a very resistant and durable that has been made with components of anodised aluminium. To ensure the robustness of the total structure, it is only possible to combine one extension per column. It has dimensions of 1500 x 110 mm x 127

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

VERSION

2 sides

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete. Column secured by applying pressure to the ceiling slab using a telescopic guide.

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053101933

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
7.7

PRODUCT NET WEIGHT
7.7

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053101933

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
3006

PACKAGING WIDTH
119

PACKAGING LENGTH
139

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.497

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
7.7

PACKAGING WEIGHT UNIT
KGM