

Modular Luminaire 730 120x10 3000 K General ON-OFF

REF. 73062040-883



BASIC INFORMATION

DESCRIPTION

For those that need quality lighting with great durability, we present the modular luminaire 730 120x10 of 3000 K. With on/off control, its emission of 3400 lumens and its consumption of 34.5 W makes it a clearly efficient luminaire.

It has a service life defined by L70>100,000 h at 25°C and L90>50,000 h at 25°C, and a CRI of 80. The finish is white and it has a guarantee of 5 years. The driver is included and powered with 230 V 50/60 Hz.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LUMENS (LM)

3400 lm

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS/W

3400lm/ 34,5W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100.000 h at 25°C

OPTICS

General

POWER SUPPLY (V~)

230 V~

L90 (°C)

50.000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

100°

POWER (W)

34.5 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

99 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted, Concealed ceiling, Semi-concealed ceiling, Flush-mounted

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053204320

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3.1

PRODUCT NET WEIGHT

2.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053204320

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

87

PACKAGING WIDTH

110

PACKAGING LENGTH

1215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

11627550

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3.1

PACKAGING NET WEIGHT

2.8

PACKAGING WEIGHT UNIT

KGM