

PD-12 HF+LUX BT Mesh surface On/Off white IP54

REF. 89214133-230



BASIC INFORMATION

DESCRIPTION

Surface presence and light detector HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 12 m and the radial detection range is 12 m.

The light regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The configuration of the detector is done via Bluetooth application.

It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection grade, and dimensions: 123 x 123 x 57 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342527

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.386

PRODUCT NET WEIGHT

0.273

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342527

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.386

PACKAGING NET WEIGHT

0.273

PACKAGING WEIGHT UNIT

KGM