

Luminaire HOLE 25 Flush mount 2700K Flood Black CRI90

REF. 91410912-288



BASIC INFORMATION

FINISH

Black

APPLICATION

Flush mount

ETIM CLASS

EC001744

MATERIAL

Aluminium

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LUMENS (LM)

266 lm

IP RATING

IP44

DRIVER INCLUDED

No

LUMENS/W

266

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

11,3 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

RAL

9005

L90 (°C)

40.000h at 25°C

POWER (W)

3.5 W

COLOR TEMPERATURE (K)

3000 K

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

REGULATIONS

Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod. | EN 62717:2017 + A2:2019 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547076383

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547076383

PACKAGING VOLUME

807500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

85

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS WEIGHT

0.26

PACKAGING LENGTH

190

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.14