2-way switch with key 2.5A 250V~ with 2 positions (key removable in both positions) and welding terminal connection ivory Simon 27 Play

REF. **27521-62**



BASIC INFORMATION

DESCRIPTION

2-way switch with key 2 positions (removable in both positions) and welding enbornamiento of type of the Simon 27 Play series. This 2-way switch has a current of 2.5 A and a voltage of 250V and is suitable both for surface and flush mounting. It is a 2-way switch is compatible with the frames of the ranges of Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. Supports a cable section with a 0.5 m and stripping of 7 mm and can be installed in places with a temperature located between 5 and 40ºC, although it supports extreme temperatures of between -25 to 50ºC. For its manufacturing has been followed by the standard EN 61058-1: 2002 + A2: 2008 + EN 50581: 2012 and is made of metal components with halogen-free insulation and thermoplastic trim. It measures 45x45mm and to clean it will only need a soft, dry cloth and never use abrasive cleaners containing chlorine.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with cover

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and key is removable in both positions.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

0,5 mm

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

No

CURRENT (A)

2,5 A

IP RATING

IP20

KEY-REMOVAL POSITION

Both positions

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Key

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

CLAW

Included

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN IEC 61058-1:2018 |EN 61058-1-1:2016|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053082126

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.099

PRODUCT NET WEIGHT
0.099

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053082126

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.329

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.095

PACKAGING NET WEIGHT
0.099

PACKAGING WEIGHT UNIT
KGM