Double German socket outlet pre-wired monoblock IP55 16A 250V~ with safety device and quick term. conn. System grey Simon 44 Aqua

REF. **4490433-035**



BASIC INFORMATION

DESCRIPTION

Covers and rockers in different colours, in grey, in aluminium, in pistachio green or in a stylish red. All kinds of colors that adapt to different environments and ideal for all types of structures, in particular outdoor areas (swimming pools, washrooms, industrial, sports facilities, terraces of all kinds, gardens, lofts ...) AND is that the products of the series Simon 44 Aqua are specially designed for areas with risk permanent contact with the water or dust. If you are looking for a socket outlet for outdoor areas, you may want to this socket outlet in Schuko format and pre-wired monoblock double version (IP55 16 Amps and 250 Volt voltage) includes a safety device for the protection of the smallest of the house and quick terminal connection, being its installation really simple and very easy. The finish, this time, is grey, so if you are looking for a design that does not stand out too much on the surface-mounted on the wall, this may be a good option. Simon proves, with this collection, which has solutions for all types of problems.

FINISH

Grey

PACKAGING CONTENTS

Socket outlet, base and frame with cover

ETIM CLASS

EC000125

COMPATIBILITY

Simon 27 mechanisms

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
2,5 mm

NUMBER OF POSSIBLE ELEMENTS
2 elements

FORMAT
Schuko

IK CLASSIFICATION
07

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP55

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

MONOBLOCK
Yes

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
7035

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

INSTALLATION DIRECTION
Vertical

INSTALLATION TYPE
Suitable for surface mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.347

PRODUCT NET WEIGHT
0.347

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053069912

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
86

PACKAGING WIDTH
155

PACKAGING LENGTH
306

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4.079

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
1.735

PACKAGING NET WEIGHT
1.735

PACKAGING WEIGHT UNIT
KGM