

Back kit for 2 elements with 1 two-way push-button switch and 1 schuko socket integrated with USB charger type A Simon 100

REF. 10010216-039



BASIC INFORMATION

DESCRIPTION

Vertical back kit for 2 elements with 1 push-button switch and 1 USB charger of the Simon 100 series. This kit has a switch current of 10 AX and USB 2.1, A. The type of emborning is in the switch, by cut, 1 click and in USB it is screw-based. With regard to the type of activation of the device, it is given by push-button and insertion. It has a voltage of 250 V~.

This product is of standard type and in its elaboration the following regulations have been followed: directive 2014/35/UE LVD + directive 2014/30/UE EMC + directive 2011/65/UE RoHS + EN 50581: 2012 + EN 60669-2-1: 2004 + EN 60669-2-1: 2004 A1: 2009 + EN 60669-2-1: 2004 A12: 2010 * 6 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950-1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3 + ETSI-EN 301489-34 v14.1 * 3 + IEC 60884-1 Ed 3.2 * 1.

This kit features a vertical installation. For proper maintenance, it must be preserved in a temperature range of 5° C to 40° C for operation and in a temperature range of -25° C to 50° C for proper storage.

FINISH

Black

COMPATIBILITY

Front Kit Simon 100

ETIM CLASS

EC002846

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

TYPE OF MECHANISM

Push button rocker
switch/Insertion

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

2 elements

MONOBLOCK

No

USB CURRENT (A)

2,1 A

INDICATOR FUNCTION

No

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

VERSION

2 elements

CURRENT (A)

10 AX

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

2-way Switch: 1 click connection
(1 click®)

TYPE OF TERMINAL

CONNECTION - FUNCTION 2

USB: Screw

KIT INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010*6 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053206379

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.24

PRODUCT NET WEIGHT

0.24

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053206379

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

88

PACKAGING LENGTH

158

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1042800

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.24

PACKAGING NET WEIGHT

0.24

PACKAGING WEIGHT UNIT

KGM