

Euro-American socket gloss white Simon 100

REF. 10000439-130



BASIC INFORMATION

FINISH

Gloss white

COMPATIBILITY

Frames Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	NOMINAL VOLTAGE (V~) 127/250 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 0 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	POWER SUPPLY (V~) 127/250 V~
FORMAT Euro-American	TYPE OF MECHANISM Insertion	STORAGE TEMPERATURE RANGE (°C) -25 - 75 °C
INDICATOR FUNCTION No	MONOBLOCK No	VERSION Unique

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 10	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX universal	INSTALLATION TYPE Suitable for flush mounting
CLAW	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004 + IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053192290

PACKAGING VOLUME
1221000

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
5

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
75

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.26

PACKAGING WIDTH
88

PACKAGING NET WEIGHT
1.275

PRODUCT NET WEIGHT
0.255

PACKAGING LENGTH
185

PACKAGING WEIGHT UNIT
KGM

