

MD-9 180° PIR+LUX BT Mesh wall surface On/Off white IP54

REF. 89202142-330



BASIC INFORMATION

DESCRIPTION

Surface-mounted PIR motion and brightness detector. The recommended installation height is 2 m, with a maximum height of 2.5 m. It has a detection angle of 180 ° and an opening angle of 90 °. The tangential detection range is 9 m and the radial detection range is 6 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 5 s - 60 min. The detector configuration is done via Bluetooth application.

It features TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W (500 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 40 °C.

White finish, IP 54 protection rating, and dimensions: 116 x 116 x 42 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053358580

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.33

PRODUCT NET WEIGHT

0.25

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053358580

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

90

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.33

PACKAGING NET WEIGHT

0.25

PACKAGING WEIGHT UNIT

KGM