

Spotlight 615 rail 2700 K Wide Flood white DALI

REF. 61500330-482



BASIC INFORMATION

APPLICATION

Accent lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LUMENS (LM)

2000 lm

IP RATING

IP20

DIRECTIONAL

Yes

LUMENS/W

2000lm/ 25W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

DRIVER INCLUDED

Yes

OPTICS

Wide Flood

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

2700 K

L90 (°C)

50,000 h at 25 °C

POWER (W)

25 W


CONTROL

DALI

LIGHTING EFFICIENCY (LM/W)

80 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase adjustable rail

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053207208

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.846

PRODUCT NET WEIGHT

0.635

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053207208

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

84

PACKAGING WIDTH

177

PACKAGING LENGTH

296

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4400928

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.846

PACKAGING NET WEIGHT

0.635

PACKAGING WEIGHT UNIT

KGM