

Movement detector switch from 40 to 300W/VA 230 V~ white Simon 75

REF. 75340-30



BASIC INFORMATION

DESCRIPTION

Motion detector switch in white colour of the Simon 75 series with a power of 230 V and typology IR / Sound of 50-60 Hz. It has a timer for disconnection between 4 seconds and 10 minutes and is a switch suitable for flush mounting. It has an element and supports a cable section of 1.5 to 2.5 mm with a stripped 8 mm and it works perfectly in places with a temperature located between 0 to 35 ° C, although it is capable of withstanding temperatures of 20 to 70, approximately. Its design is the regulations UNE-EN -60669-2-1: 2005 + A1: 2010 + A12: 2011 and is made of electronic components with halogen-free thermoplastic insulation. Its clamping is screwed and its type of operation by detecting and also has a switch-off timer of between 4 seconds and 10 minutes and is suitable both for surface and flush mounting and can also, the installation of 2 units in parallel.

FINISH

White

COMPATIBLE WITH MECHANICAL 2-WAY/CROSSOVER SWITCH

No

COMPATIBLE WITH MECHANICAL SWITCH

No

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature and Simon 82 frames

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

PACKAGING CONTENTS

Movement detector and instruction sheet

ETIM CLASS

EC000133

REMARKS

Allows 2 units to be installed in parallel.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONTACTS

3

NUMBER OF CONTROLLABLE CIRCUITS

1

DISCONNECTION TIMER

4 seconds to 10 minutes

COMPATIBLE WITH ELECTRONIC AUXILIARY

No

COMPATIBLE WITH HALOGENS WITH ELECTRONIC TRANSFORMER (W)

No

NUMBER OF POSSIBLE ELEMENTS

1 element

COMPATIBLE WITH FLUORESCENT LAMPS WITH 1-10V DIMMABLE ELECTRONIC BALLAST

No

COMPATIBLE WITH FLUORESCENT LAMPS (VA)

No

FREQUENCY

50 - 60 Hz

INDICATOR FUNCTION

Yes

IP RATING

IP20

COMPATIBLE WITH LOW CONSUMPTION (W)

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM QUANTITY PER CIRCUIT

2

TYPE OF MECHANISM

Detection

COMPATIBLE WITH MOTORS (VA)

No

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

POWER SUPPLY (V~)

230 V~

APPROXIMATE RANGE (M)

6 m

STORAGE TEMPERATURE RANGE (°C)

20 - 70 °C

TYPE

IR/Sound

VERSION

Single

NUMBER OF WIRES

2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

8

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.195

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

518400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053014165

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

518400

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.195

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

81

PACKAGING NET WEIGHT

0.195

UNITARY PACKAGING GROSS

WEIGHT

0.195

PACKAGING WIDTH

80

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

80