

IP66 mechanism holder unit with safety lock for a function of 1 element and 1 RJ45 Keystone clipping in stainless steel Simon K45

REF. KSE01SEC/23/72



BASIC INFORMATION

DESCRIPTION

With the range update, its equivalent for the new version is the KGH101SEC/72 reference.

FINISH

Stainless steel

COMPATIBILITY

Functions Simon K45

MATERIAL

Stainless steel

ETIM CLASS

EC000024

TECHNICAL INFORMATION

DUST SHUTTER

No

KIT AVAILABILITY

No

MAXIMUM LOAD (KG)

1000kg

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

IP RATING

IP66

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053297780

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.354

PRODUCT NET WEIGHT

0.354

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053297780

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

160

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1664000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.404

PACKAGING NET WEIGHT

0.354

PACKAGING WEIGHT UNIT

KGM