

Individual fastening bracket on DIN rail for Ofiblock Plus and Ofiblock Compact aluminium profiles Simon K45

REF. KSF5



BASIC INFORMATION

DESCRIPTION

Individual fastening bracket on DIN rail for Ofiblock Plus aluminium profiles and Ofiblock Compact of the series Simon K45. It is made of thermoplastic material and self-extinguishing halogen-free that guarantees no flame spread in case of fire, in case of fire, and low toxicity in case of smoke. Complies perfectly with the regulation European UNE -s 60.670-23 and can be position, place in rooms with a temperature located between the -5 to 60 ° C, although it is able to withstand extreme temperatures and high. Its dimensions are 44 x 46 x 36,5 mm and to clean this bracket, just have to do it with a soft and dry cloth, without having to use never abrasive cloths or cleaners that contain chlorine in their formulation, as they could cause the bracket is damaged and that does not fulfill its function perfectly.

FINISH

Galvinised steel

MATERIAL

Metal

COMPATIBILITY

Simon K45 Ofiblock Plus and Ofiblock Compact aluminium profiles

PACKAGING CONTENTS

Individual fastening bracket on DIN rail and installation manual.

ETIM CLASS

EC001024

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+125°C (according to standard
IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+850 °C (according to standard
IEC 60670)

TYPE OF FASTENING

By connecting the bracket through the rear DIN rail on the Ofiblock profile and subsequent fastening on the DIN rail itself.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436046498

PRODUCT NET WEIGHT

0.035

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

288800

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436046498

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.04

UNITARY PACKAGING VOLUME

288800

PACKAGING HEIGHT

50

PACKAGING NET WEIGHT

0.035

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

76

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.035

PACKAGING LENGTH

76