

Linear Light module 860 1200 4000 K

REF. 86001300-384



BASIC INFORMATION

APPLICATION

Residential

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC000996

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

COLOR TEMPERATURE (K)

4000K

LUMENS/W

120 lm/W

IP RATING

IP20

CONTROL

DALI

MACADAM STEPS

< 3 Step MacAdam

OPERATING TEMPERATURE RANGE (°C)

Ta Max 35°C

CRI

80

OPTICS

Opal

POWER SUPPLY (V~)

220/240 V~

LUMENS (LM)

2175 lm

POWER (W)

18 W

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053298909

UNITARY PACKAGING HEIGHT

60

UNITARY PACKAGING WIDTH

60

UNITARY PACKAGING LENGTH

1220

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

4392000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

1.05

PRODUCT NET WEIGHT

0.77

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053298909

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

60

PACKAGING LENGTH

1220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4392000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.05

PACKAGING NET WEIGHT

0.77

PACKAGING WEIGHT UNIT

KGM