

Projector 889 20W 4000K

REF. 88931038-884



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for showcase and facade lighting, robust, adjustable and designed for high performance in commercial applications. Available in different power ratings, the outdoor projector 889 allows you to select the appropriate model according to the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 4000K. Power: 20W. Lumens: 1600lm. Efficiency: 80lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 127 mm x 107 mm x 28 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

80 lm/W

LUMENS (LM)

1600 lm

OPTICS

Symmetric

POWER (W)

20 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440513

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053440513

PACKAGING VOLUME

13537500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

250

PACKAGING GROSS WEIGHT

4.18

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

190

PACKAGING NET WEIGHT

0.188

UNITARY PACKAGING GROSS
WEIGHT

0.209

PACKAGING LENGTH

285

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.188