Cover and trim frame for Teleblock telescopic profile matt chrome Simon K45

REF. **KTLA1/31**



BASIC INFORMATION

DESCRIPTION

This cover and trim frame are designed for Teleblock telescopic profile, they are finished in matt chromed and is included in the series Simon K45. The parts are manufactured in thermoplastic material and self-extinguishing halogen-free that prevents, in the event of a fire, the propagation of the fire, as well as to reduce the toxicity having smoke. The set it is suitable for flush mounting in furniture and stands out for its thermal resistance, although the ideal thing is to install it in environments between -5 and 60 ° C for better preservation. It is available in graphite and matt chromed, although there is the other finishes may be supplied to order. As for its maintenance, you can use a dry, soft textured cloth, avoid, in addition, the use of abrasive cleaning products containing chlorine, as they could damage these mechanisms.

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Cover, trim frame, rubber gland and installation manual.

ETIM CLASS

EC002649

REMARKS

Other finishes may be supplied (on request).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections. Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections.

AVAILABLE IN
Available in graphite and matt chrome

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
No tools needed

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
By the threading at 45° to the cover on the top closure supplied with the Simon Teleblock K45 telescopic profile.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for embedding in furniture.

SECURING POSSIBILITIES
Its design enables wiring and cable passage, allowing the telescopic profile to be lowered, integrating into the furniture, keeping connections active and serving as a cable pass-through.

MOUNTING WITHOUT ACCESSORIES
The cover and decorative mirror are supplied with all necessary installation materials, without needing additional references for attachment.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052130

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
453024

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.081

PRODUCT NET WEIGHT
0.081

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052130

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
132

PACKAGING WIDTH
26

PACKAGING LENGTH
132

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
453024

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.081

PACKAGING NET WEIGHT
0.081

PACKAGING WEIGHT UNIT
KGM