

**2-way switch with key 2.5A 250V~ 3 positions (key
removable in rest position) and welding terminal
connection ivory Simon 27 Play**

REF. 27523-62



BASIC INFORMATION

DESCRIPTION

The 2-way switch of the Simon Play 27 series is the perfect if what you are looking for is skew a current of a circuit or directly suspend it. It is suitable for elements of up to 2.5 A current and 250 volts and works by key of 3 positions. It is necessary to highlight the key is removable in rest position. The rocker operation is carried out by welding and the device is very easy to install, by means of recessed or directly on the surface-mounted, offering two options to the user. It comes in an original and stylish finished in ivory colour. It measures 45 x 45 millimetres and is made up of two modules, in addition, it is a product that stands out for its manufacturing materials that give it a high resistance and extra security. These are metal elements, halogen-free, and the trim is made of thermoplastic, the features of these materials make the final product is able to work in optimum low temperatures very low and high.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with cover

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

0,5 mm

KEY-REMOVAL POSITION

Standby

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VERSION

Single

CURRENT (A)

2,5 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

CLAW

Included

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and
Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053082140

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053082140

PACKAGING VOLUME

0.598

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

81

PACKAGING GROSS WEIGHT

0.095

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

82

PACKAGING NET WEIGHT

0.095

UNITARY PACKAGING GROSS
WEIGHT

0.095

PACKAGING LENGTH

90

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.095