

Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6A FTP white Simon 500 Cima

REF. 50001085-030



BASIC INFORMATION

DESCRIPTION

The plate of voice and data flat plate with dust cover with 1 element with RJ45 category 6A FTP offers a few simple but elegant finishes white in colour and is part of the Simon 500 Cima series. Its measures are 50x50x54 mm and has a thickness of 44 mm. This part also includes the RJ45 connectors, clips for fastening in vertical and horizontal enclosures without the need of adapter. And not only that, thanks to its manufacture with metal components with insulation coated self-extinguishing halogen-free thermoplastic, we guarantee that there are no flame spread in case of fire in case of fire and low toxicity if any smoke. That is why the collection Simon 500 Cima is presented as one of the most demanding performances in terms of security., and that is that we endeavor by always offer the best of the best for the satisfaction of our customers.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, RJ45 connector category 6A FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6A FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097953

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.052

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.04

PRODUCT NET WEIGHT

0.052

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

